



SAFETY DATA SHEET

According to EC Directive 1907/2006/EC, Article 31

Revision Date: 20/September/2013

Product Code: M5

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: CAB-O-SIL® Untreated Fumed Silica

Synonyms: Silicon Dioxide, Synthetic Amorphous Silica, Pyrogenic (Fumed) Amorphous Silica

REACH Registration Number: 01-2119379499-16

This SDS is valid for the following grades: CAB-O-SIL® Fumed Silica, L-50, L-60, L-90, LM-130, LM-150, M-5, M-5K, PTG, MS-55, H-5, H-7D, HS-5, EH-5, LM-130D, LM-150D, M-7D, MS-75D, S-17D, HP-60, M-8D, EL-1000, EL-2000, MS-35, H300, EL-90, EL-100, ELM-150

Use of the Substance/Preparation: Rheological control, Flow agent, Reinforcing agent in: Coatings, Adhesives, Various

Supplier:

Cabot GmbH Kronenstrasse 2 79618 Rheinfelden GERMANY Tel: (+49) 7623.7070 Fax: (+49) 7623.707 530	Cabot Carbon, Ltd. Sully Moors Road Sully, Vale of Glamorgan CF64 5RP Wales, UNITED KINGDOM Tel: (+44) 1446.736999 Fax: (+44) 1446.737123	Cabot Corporation 700 E U.S. Highway 36 Tuscola, IL 61953-9643 UNITED STATES Tel: 1-217-253-3370 Fax: 1-217-253-5586	Cabot Corporation 157 Concord Road Billerica, MA 01821 UNITED STATES Tel: 1-978-663-3455 Fax: 1-978-670-6955
Cabot Bluestar Ltd. Xinghuo Industrial Garden Yongxiu County, Jiujiang City 330319 Jiangxi Province, CHINA Tel: (86-792) 3170163 Fax: (86-792) 3170122	Cabot Corporation 3603 South Saginaw Road Midland, MI 48640 UNITED STATES Tel: 1-989-495-0030 Fax: 1-989-495-2139		

E-Mail Address: SDS@cabotcorp.com

Emergency Telephone Number: Germany (Cabot GmbH - Rheinfelden): (+49) 7623-7070
UK (Cabot Carbon Ltd - Barry): (+44) 1446-709 641
Canada: CANUTEC 1-613-996-6666
US: CHEMTREC: +1-703-527-3887 or 1-800-424-9300
China: (86-792) 3170175
CHEMTREC China: 4001-204937

2. HAZARDS IDENTIFICATION

Pictogram: Not applicable

Indication of danger: Not a hazardous substance according to EC-Directive 67/548/EC, its various amendments and adaptations and EC-Regulation 1272/2008 (CLP)

Signal Word: Not applicable

Hazard Statement(s): Not applicable

Precautionary Statement(s): Not applicable

Principle Routes of Exposure: Inhalation, Skin contact, Eye contact

POTENTIAL HEALTH EFFECTS

Eye Contact: May cause mechanical irritation.

Skin Contact: Repeated exposure may cause skin dryness or cracking.

Inhalation: Dust may be irritating to respiratory tract. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. See also Section 8.

Ingestion: Health injuries are not known or expected under normal use.

Carcinogenic Effects: Does not contain any substances greater than 0.1% listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union). See also Section 11.

Target Organ Effects: Lungs

Medical Conditions Aggravated by Exposure: Asthma, Respiratory disorder

Potential Environmental Effects: No special environmental precautions required.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	EINECS/ELINCS Number	Weight %	EU Classification
Synthetic Amorphous, Pyrogenic Silica	112945-52-5	*	> 99.9	None

* See Section 15.

4. FIRST AID MEASURES

Skin Contact: Wash thoroughly with soap and water. Seek medical attention if redness, swelling, itching, or burning occurs.

Eye Contact: Flush eyes immediately with large amounts of water for 15 minutes. Seek medical attention if redness, swelling, itching, burning or visual disturbances occur.

Inhalation: If cough, shortness of breath or other breathing problems occur, move to fresh air. Seek medical attention if symptoms persist. If necessary, restore normal breathing through standard first aid measures.

Ingestion: Do not induce vomiting. If conscious, give several glasses of water. Never give anything by mouth to an unconscious person.

Notes to Physician: Treat symptomatically.

5. FIRE AND IGNITION INFORMATION

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special Protective Equipment for Firefighters: Wear suitable protective equipment. In the event of fire, wear self-contained breathing apparatus.

Specific Hazards: Product resists ignition and does not promote flame spread.

Hazardous Decomposition and/or None.

Combustion Products:

Risk of Dust Explosion: This material is an inorganic dust and will not create nor support conditions that would result in a dust explosion or fire.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Avoid dust formation. Ensure adequate ventilation. Use personal protective equipment. See also Section 8.

Methods for Cleaning Up: Clean up promptly by vacuum. Use a suitable vacuum cleaner. Do not create a dust cloud by using a brush or compressed air. Pick up and transfer to properly labelled containers. See Section 13.

Environmental Precautions: No special environmental precautions required. Local authorities should be advised if significant spillages cannot be contained.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated. Do not create a dust cloud by using a brush or compressed air. Take precautionary measures against static discharge. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations.

Storage: Keep containers tightly closed in a dry and well-ventilated place. Do not store together with volatile chemicals as they may be adsorbed onto product. Keep at ambient temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

Exposure limits for silica are stated below. In its facilities globally, Cabot Corporation manages to the Germany TRGS 900 occupational exposure limit of 4 mg/m³, TWA, Inhalable fraction.

Exposure limits for dust are stated below.

Amorphous Silica, The regulatory exposure limits are found under the general silica, CAS RN 7631-86-9:	Australia:	2 mg/m ³ , TWA, Respirable
	Austria MAK:	4 mg/m ³ , TWA, Inhalable fraction
	Finland:	5 mg/m ³
	Germany TRGS 900:	4 mg/m ³ , TWA, Inhalable fraction
	India:	10 mg/m ³ , TWA
	Ireland:	2.4 mg/m ³ , TWA, Respirable dust
	Norway:	1.5 mg/m ³ , TWA, Respirable dust
	Switzerland:	4 mg/m ³ , TWA, Inhalable
	UK WEL:	6 mg/m ³ , TWA, Inhalable
		2.4 mg/m ³ , TWA, Respirable
	US OSHA - PEL:	6 mg/m ³ (54 FR2701)

Dust, or Particulates Not Otherwise Specified:	Belgium:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ TWA, Respirable
	China:	8 mg/m ³ , TWA 10 mg/m ³ , STEL
	France:	10 mg/m ³ , TWA Inhalable dust 5 mg/m ³ , TWA Respirable dust
	Italy:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, respirable
	Malaysia:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
	Spain:	10 mg/m ³ , VLA, Inhalable 3 mg/m ³ , VLA, Respirable
	US ACGIH - TLV:	10 mg/m ³ , TWA, Inhalable 3 mg/m ³ , TWA, Respirable
	US OSHA - PEL:	15 mg/m ³ , TWA, Total dust 5 mg/m ³ , TWA, Respirable

MAK: Maximale Arbeitsplatzkonzentration (Maximum Workplace Concentration)

OEL: Occupational Exposure Limit

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit

TLV: Threshold Limit Value

TRGS: Technische Regeln für Gefahrstoffe (Technical Rule for Hazardous Materials)

TWA: Time Weighted Average

US ACGIH: United States American Conference of Governmental Industrial Hygienists

US OSHA: United States Occupational Safety and Health Administration

VLA: Valore Limite Ambientales (Environmental Limit Value)

WEL: Workplace Exposure Limit

DNEL: As required under the EU Registration, Evaluation and Authorization of Chemicals (REACH) Regulation, the Synthetic Amorphous Silica REACH Consortium (of which Cabot Corporation is a member) developed a Derived No Effect Level (DNEL) for Synthetic Amorphous Silica of 4 mg/m³ inhalable (Germany TRGS 900 occupational exposure limit)

PNEC: Not applicable

ENGINEERING CONTROLS Ensure adequate ventilation to maintain exposures below occupational limits. Provide appropriate exhaust ventilation at machinery and at places where dust can be generated.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: Approved respirator may be necessary if local exhaust ventilation is not adequate.

Hand Protection: Repeated exposure may cause skin dryness or cracking. Use appropriate protective barrier before handling.

Eye Protection: Wear eye/face protection.

Skin and Body Protection: Wear suitable protective clothing.

Other: Handle in accordance with good industrial hygiene and safety practice. Emergency eyewash and safety shower should be located nearby.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White Powder

Odor: None.

Odor Threshold:	Not applicable
pH:	3.6 - 4.5
Density:	2.2 g/cm ³ @ 20°C
Specific Gravity:	2.2 @ 20°C
Bulk Density:	30-150 kg/m ³
Vapor Density:	Not applicable
Vapor Pressure:	Not applicable
Boiling Point/Range:	2230°C
Melting Point/Range:	1700°C
Water Solubility:	Poorly soluble
% Volatile (by Weight):	Not applicable
Evaporation Rate:	Not applicable
Viscosity:	Not applicable
Partition Coefficient (n-octanol/water):	Not determined
Flash Point:	Not determined
Explosion Limits in Air - Upper (g/m³):	Not applicable
Explosion Limits in Air - Lower (g/m³):	Not applicable
Flammability classification	Not applicable
Autoignition Temperature:	Not applicable
Decomposition Temperature:	Not determined
Oxidizing Properties:	Not applicable
Explosive properties	Not applicable

10. STABILITY AND REACTIVITY

Stability:	Stable
Hazardous Polymerization:	Hazardous polymerization does not occur.
Conditions to Avoid:	None reported.
Hazardous Decomposition and/or Combustion Products:	None.
Static Discharge Effects:	Take precautionary measures against static discharges. Avoid dust formation. All metal parts of the mixing and processing equipment must be earthed/grounded. Ensure all equipment is electrically earthed/grounded before beginning transfer operations. This material is an inorganic dust and will not create nor support conditions that would result in a dust explosion or fire.

11. TOXICOLOGICAL INFORMATION

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Oral LD50: LD50/oral/rat = > 5000 mg/kg.

Inhalation LC50: Due to the product's physical characteristics, no suitable testing procedure is available.

Dermal LD50: LD50/dermal/rabbit = > 2000 mg/kg.

STOT - Single Exposure: None observed.

Eye Irritation: Draize score 1.0/110 @ 24 hr.

Skin Irritation: Primary irritation index = 0/8 @ 24 hr

SUBCHRONIC TOXICITY

No significant treatment-related adverse effects were observed in rats administered silica at doses of up to 8% silica in their diet for a duration of 2 weeks to 6 months.

STOT - Repeated Exposure: None expected

CHRONIC TOXICITY

Mutagenic Effects:

Not mutagenic in AMES Test, Negative in the unscheduled DNA synthesis assay, Negative in the chromosome aberration test in Chinese hamster ovary (CHO) cells.

Reproductive Toxicity: Did not show teratogenic effects in animal experiments. According to experience not expected.

Sensitization: According to experience, sensitization is not expected.

Synergistic Materials: None reasonably foreseeable.

Carcinogenic Effects: Does not contain any substances greater than 0.1% listed by IARC (International Agency for Research on Cancer), NTP (National Toxicology Program), OSHA (Occupational Safety and Health Administration), ACGIH (American Conference for Governmental Industrial Hygienists) or EU (European Union)

Aspiration Hazard: Not determined

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: Fish (Brachydanio rerio) LC50 (96 h): > 10,000 mg/l; (Method: OECD 203)

ENVIRONMENTAL FATE

Mobility: Not expected to migrate.

Bioaccumulation: Not expected due to physicochemical properties of the substance.

Persistence / Degradability: The methods for determining biodegradability are not applicable to inorganic substances

Distribution to Environmental Compartments: Not determined.

PBT and vPvB Assessment: This substance does not fulfill the criteria for PBT or vPvB

Other adverse effects: No other data are available

13. DISPOSAL CONSIDERATIONS

Disclaimer: Disclaimer: Information in this section pertains to the product as shipped in its intended composition as described in Section 3 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations.

Dispose in accordance with applicable legislations.

14. TRANSPORT INFORMATION

UN Number: Not regulated

UN Proper Shipping Name: Not regulated

UN Shipping Class: Not regulated

UN Packing Group: Not regulated

IMDG (International Maritime Organization's Dangerous Goods Code):

Use UN classification listed above.

IATA:

Use UN classification listed above.

15. REGULATORY INFORMATION

Regulatory information is found under the general silica: CAS RN 7631-86-9, EINECS RN 231-545-4.

Indication of danger: Not a hazardous substance according to EC-Directive 67/548/EC, its various amendments and adaptations and EC-Regulation 1272/2008 (CLP).

EU Chemical Safety Assessment:

Per Article 14.1 of the REACH Regulation a Chemical Safety Assessment has been carried out.

EU Exposure Scenarios

Per Article 14.4 of the REACH Regulation no exposure scenario has been developed as the substance is not hazardous.

International Inventories

All components of this product are listed on or exempt from the following inventories:

- YES - Australian Inventory of Chemical Substances (AICS)
- YES - Canadian Domestic Substances List (DSL)
- YES - Chinese Inventory
- YES - European Inventory of Existing Commercial Chemical Substances (EINECS)
- YES - Japanese Existing and New Chemical Substances (ENCS)
- YES - Korean Existing Chemicals List (KECL)
- YES - New Zealand Hazardous Substances and New Organisms Act (HSNO)
- YES - Philippine Inventory of Chemicals and Chemical Substances (PICCS)
- YES - United States Toxic Substances Control Act (TSCA) Inventory

Germany Water Endangering Class (WGK) Class
Chemical Name

Synthetic Amorphous, nwg (not water endangering): 849
Pyrogenic Silica

Switzerland Giftklasse (Poison Class) Toxic Category

Chemical Name

Synthetic Amorphous, -- (tested and found to be not toxic): G-8311
Pyrogenic Silica

16. OTHER INFORMATION

Prepared by: Cabot Corporation - Safety, Health and Environmental Affairs
Revision Date: 20/September/2013
Previous Revision Date: 13/April/2012

Reason for Revision: Revisions to Section(s) 1,8,9, New product

Disclaimer:

The information set forth is based on information that Cabot Corporation believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and Cabot assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

® and 'TM' indicate trademarks of the Cabot Corporation.