## NOVOCS™ Gloss & NOVOCS™ Matte Zero-VOC Silicone Solvent Fluids



**NOVOCS™** solvents are low viscosity silicone solvents that evaporate quickly. **NOVOCS™** solvents contain **no VOC's. NOVOCS™** is particulary useful in thinning down **Psycho Paint®** silicone paint base to apply via brush or airbrush to cured platinum silicone rubber props and prosthetics.

When used as a solvent for thinning silicone paints or surface coatings, **NOVOCS™ Gloss** will leave a **gloss finish**.

**NOVOCS™** Matte will leave a matte finish on the surface of cured silicone.

WARNING - FLAMMABLE Liquid and vapor. Keep away from ignition sources and follow precautions for handling flammables.

**Directions:** Materials should be stored and used in a warm environment (73°F / 23°C). This material has a limited shelf life and should be used as soon as possible. Wear safety glasses, long sleeves and rubber gloves to minimize contamination risk.

**Important:** Shake NOVOCS® Container Well Before Using.

Mix the A and B components of two component silicone sytems before adding **NOVOCS™**. Add the desired proportion of **NOVOCS™** solvent to create a thinner silicone mixture which can be brushed or airbrushed onto the surface of a cured silicone casting.

Increasing the amount of **NOVOCS™ Matte** will create a more matte finish on the cured surface.

## **Example Recommended Ratios For Use:**

- When adding to Psycho Paint, add between 200%-400% NOVOCS™ solvent by weight
- When adding to Sil-Poxy, add between 300%-500% NOVOCS™ solvent by weight

Because no two applications are quite the same, a small test application to determine suitability for your project is recommended if performance of this material is in question.

## **Safety First!**

The material safety data sheet (MSDS) for this or any Smooth-On product should be read before using and is available on request or on our website at www.smooth-on.com. All Smooth-On products are safe to use if directions are read and followed carefully. *Keep Out of Reach Of Children*.

**IMPORTANT** - The information contained in this bulletin is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained from the use thereof, or that any such use will not infringe a copyright or patent. User shall determine suitability of the product for the intended application and assume all associated risks and liability.



Call Us Anytime With Questions About Your Application.

Toll-free: (800) 381-1733 Fax: (610) 252-6200

The new **www.smooth-on.com** is loaded with information about mold making, casting and more.