



## SAFETY DATA SHEET

### WEST SYSTEM G/flex 655 Hardener

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** WEST SYSTEM G/flex 655 Hardener  
**Product number** 655B  
**UFI** UFI: KM90-00YY-500E-5U98

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Hardener.  
**Uses advised against** No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Wessex Resins & Adhesives  
Cupernham House  
Cupernham Lane  
Romsey  
Hampshire  
S051 7LF  
Tel: +44(0)1794 521111  
Fax: +44(0)1794 521271  
info@wessex-resins.com

**EU IMPORTER** Wessex Resins and Adhesives Limited, First Floor, 43-40 Sir John Rogerson's Quay, Dublin 2, Dublin, Ireland Tel: +353 15256758

##### 1.4. Emergency telephone number

**Emergency telephone** +44(0)207 858 1228

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Not Classified  
**Health hazards** Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT RE 2 - H373  
**Environmental hazards** Aquatic Chronic 3 - H412

**Human health** The product contains a sensitising substance. See Section 11 for additional information on health hazards.

**Environmental** The product is not expected to be hazardous to the environment.

##### 2.2. Label elements

## WEST SYSTEM G/flex 655 Hardener

### Hazard pictograms



### Signal word

Danger

### Hazard statements

H315 Causes skin irritation.  
 H318 Causes serious eye damage.  
 H317 May cause an allergic skin reaction.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements

P102 Keep out of reach of children.  
 P280 Wear protective gloves, eye and face protection.  
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a POISON CENTER/ doctor.  
 P501 Dispose of contents/ container in accordance with national regulations.

### Contains

Butadiene-acrylonitrile co-polymer, Triethylenetetramine, m-phenylenebis(methylamine), Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA, 2-piperazin-1-ylethylamine, tetraethylenepentamine, Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>Butadiene-acrylonitrile co-polymer</b> CAS number: 68683-29-4                      EC number: 614-706-7	<b>30-60%</b>
<b>Classification</b> Skin Sens. 1 - H317	
<b>Triethylenetetramine</b> CAS number: 112-24-3                      EC number: 203-950-6                      REACH registration number: 01-2119487919-13-0000	<b>5-10%</b>
<b>Classification</b> Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412	

## WEST SYSTEM G/flex 655 Hardener

<b>m-phenylenebis(methylamine)</b>	<b>5-10%</b>
CAS number: 1477-55-0	EC number: 216-032-5
	REACH registration number: 01-2119480150-50-XXXX
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1B - H317 Aquatic Chronic 3 - H412	
<b>Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA</b>	<b>1-5%</b>
CAS number: 1101788-77-5	
<b>Classification</b> Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317	
<b>2,4,6-tris(dimethylaminomethyl)phenol</b>	<b>1-5%</b>
CAS number: 90-72-2	EC number: 202-013-9
	REACH registration number: 01-2119560597-27-XXXX
<b>Classification</b> Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319	
<b>2-piperazin-1-ylethylamine</b>	<b>1-5%</b>
CAS number: 140-31-8	EC number: 205-411-0
	REACH registration number: 01-2119471486-30-0003
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 3 - H311 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 2 - H361 STOT RE 1 - H372 Aquatic Chronic 3 - H412	

**WEST SYSTEM G/flex 655 Hardener**

<b>tetraethylenepentamine</b> <span style="float: right;"><b>1-5%</b></span>		
CAS number: 112-57-2	EC number: 203-986-2	REACH registration number: 01-2119487290-37-0000
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411		
<b>Cashew (Anacardium occidentale) Nutshell Extract, Decarboxylated, Distilled</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 8007-24-7	EC number: 700-991-6	REACH registration number: 01-2119502450-57-0000
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317		

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin contact</b>	It is important to remove the substance from the skin immediately. Take off immediately all contaminated clothing. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.

## WEST SYSTEM G/flex 655 Hardener

**Protection of first aiders** First aid personnel should wear appropriate protective equipment during any rescue. If it is suspected that volatile contaminants are still present around the affected person, first aid personnel should wear an appropriate respirator or self-contained breathing apparatus. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation.

### 4.2. Most important symptoms and effects, both acute and delayed

**General information** See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

**Inhalation** A single exposure may cause the following adverse effects: Severe irritation of nose and throat. Symptoms following overexposure may include the following: Corrosive to the respiratory tract.

**Ingestion** May cause sensitisation or allergic reactions in sensitive individuals. May cause chemical burns in mouth, oesophagus and stomach. Symptoms following overexposure may include the following: Severe stomach pain. Nausea, vomiting.

**Skin contact** May cause skin sensitisation or allergic reactions in sensitive individuals. Symptoms following overexposure may include the following: Pain or irritation. Redness.

**Eye contact** Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes for the doctor** Treat symptomatically. May cause sensitisation or allergic reactions in sensitive individuals.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Severe corrosive hazard. Water used for fire extinguishing, which has been in contact with the product, may be corrosive.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Very toxic or corrosive gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

## WEST SYSTEM G/flex 655 Hardener

**Special protective equipment for firefighters** Regular protection may not be safe. Wear chemical protective suit. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. Avoid inhalation of vapours and spray/mists. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes. Avoid contact with contaminated tools and objects.

#### 6.2. Environmental precautions

**Environmental precautions** The product may affect the acidity (pH) of water which may have hazardous effects on aquatic organisms. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. This product is corrosive. Approach the spillage from upwind. Small Spillages: Absorb spillage with non-combustible, absorbent material. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

#### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. This product is corrosive. Immediate first aid is imperative. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

**Advice on general occupational hygiene** Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

## WEST SYSTEM G/flex 655 Hardener

**Storage precautions** Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

**Storage class** Chemical storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure controls/Personal protection

### 8.1. Control parameters

**Ingredient comments** No exposure limits known for ingredient(s).

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended. Wear protective gloves made of the following material: Nitrile rubber. Thickness:  $\geq 0.13$  mm. The selected gloves should have a breakthrough time of at least 0.5 hours.

#### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

#### Hygiene measures

Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. When using do not eat, drink or smoke. Wash at the end of each work shift and before eating, smoking and using the toilet. Warn cleaning personnel of any hazardous properties of the product.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Combination filter, type A2/P2.

#### Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

## WEST SYSTEM G/flex 655 Hardener

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	Amber.
<b>Odour</b>	Ammonia.
<b>Odour threshold</b>	Not determined.
<b>pH</b>	Not determined.
<b>Melting point</b>	Not determined.
<b>Initial boiling point and range</b>	> 250°C @ 760 mm Hg
<b>Flash point</b>	> 93°C Closed cup.
<b>Evaporation rate</b>	Not determined.
<b>Evaporation factor</b>	Not determined.
<b>Upper/lower flammability or explosive limits</b>	Not determined.
<b>Vapour pressure</b>	< 1 mm Hg @ °C
<b>Vapour density</b>	> 1
<b>Relative density</b>	0.99 @ 25°C
<b>Bulk density</b>	Not determined.
<b>Solubility(ies)</b>	Slightly soluble in water.
<b>Partition coefficient</b>	Not determined.
<b>Auto-ignition temperature</b>	Not determined.
<b>Decomposition Temperature</b>	Not determined.
<b>Viscosity</b>	237,000 mPa s @ 25°C
<b>Explosive properties</b>	Not determined.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.
<b><u>9.2. Other information</u></b>	
<b>Other information</b>	Not known.

### SECTION 10: Stability and reactivity

#### **10.1. Reactivity**

**Reactivity** Stable under the prescribed storage conditions.

#### **10.2. Chemical stability**

**Stability** Stable at normal ambient temperatures and when used as recommended.

#### **10.3. Possibility of hazardous reactions**

**Possibility of hazardous reactions** None known.

#### **10.4. Conditions to avoid**

**Conditions to avoid** There are no known conditions that are likely to result in a hazardous situation.

#### **10.5. Incompatible materials**



## WEST SYSTEM G/flex 655 Hardener

**Materials to avoid** Strong acids. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE oral (mg/kg)** 4,297.38

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE dermal (mg/kg)** 9,682.67

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE inhalation (dusts/mists mg/l)** 26.43

#### Skin corrosion/irritation

**Animal data** Skin Irrit. 2 - H315 Causes skin irritation.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Eye Dam. 1 - H318 Corrosivity to eyes is assumed.

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** May cause skin sensitisation or allergic reactions in sensitive individuals.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

#### **IARC carcinogenicity**

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

#### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H335 May cause respiratory irritation.

**Target organs** Respiratory system, lungs

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.

## WEST SYSTEM G/flex 655 Hardener

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### **General information**

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### **Inhalation**

Corrosive to the respiratory tract. Symptoms following overexposure may include the following: Severe irritation of nose and throat.

### **Ingestion**

May cause sensitisation or allergic reactions in sensitive individuals. May cause chemical burns in mouth, oesophagus and stomach. Symptoms following overexposure may include the following: Severe stomach pain. Nausea, vomiting.

### **Skin contact**

May cause skin sensitisation or allergic reactions in sensitive individuals. Symptoms following overexposure may include the following: Pain or irritation. Redness. Blistering may occur.

### **Eye contact**

Causes serious eye damage. Symptoms following overexposure may include the following: Pain. Profuse watering of the eyes. Redness.

### **Route of exposure**

Ingestion Inhalation Skin and/or eye contact

### **Target organs**

Respiratory system, lungs

### **Medical considerations**

Skin disorders and allergies.

### Toxicological information on ingredients.

#### Butadiene-acrylonitrile co-polymer

**Toxicological effects** No information available.

#### Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA

**Toxicological effects** No information available.

#### 2,4,6-tris(dimethylaminomethyl)phenol

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Harmful if swallowed.

**ATE oral (mg/kg)** 500.0

#### Skin sensitisation

**Skin sensitisation** Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.

#### Reproductive toxicity

**Reproductive toxicity - fertility** - NOAEL > 15 mg/kg/day, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** NOAEL > 15 mg/kg, Oral, Rat REACH dossier information. Not classified as a specific target organ toxicant after repeated exposure.

## WEST SYSTEM G/flex 655 Hardener

### 2-piperazin-1-ylethylamine

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Harmful if swallowed.

**ATE oral (mg/kg)** 500.0

#### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 866.0

**Species** Rabbit

**Notes (dermal LD<sub>50</sub>)** REACH dossier information. Harmful in contact with skin.

**ATE dermal (mg/kg)** 866.0

#### Skin corrosion/irritation

**Animal data** Dose: , 20 min, Rabbit Oedema score: Severe oedema - raised more than 1 mm and extending beyond area of exposure (4). REACH dossier information. Corrosive to skin.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Corrosive to skin. Corrosivity to eyes is assumed. No testing is needed.

#### Skin sensitisation

**Skin sensitisation** Guinea pig maximization test (GPMT) - Guinea pig: Sensitising. REACH dossier information. May cause sensitisation by skin contact.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

#### Reproductive toxicity

**Reproductive toxicity - fertility** Screening: - NOAEC 8000 mg/l, Oral, Rat P REACH dossier information.

**Reproductive toxicity - development** Developmental toxicity: - NOAEC: 8000 mg/l, Oral, Rat REACH dossier information.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** NOAEL 2000 mg/l/6hr/day, Oral, Rat REACH dossier information.

### SECTION 12: Ecological information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

#### 12.1. Toxicity

**Toxicity** Based on available data the classification criteria are not met.

#### Ecological information on ingredients.

### Butadiene-acrylonitrile co-polymer

## WEST SYSTEM G/flex 655 Hardener

**Toxicity** There are no data on the ecotoxicity of this product.

### Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA

**Toxicity** There are no data on the ecotoxicity of this product.

#### 2,4,6-tris(dimethylaminomethyl)phenol

##### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: < 240 mg/l, Freshwater fish  
REACH dossier information.

**Acute toxicity - aquatic invertebrates** LC<sub>50</sub>, 96 hours: 718 mg/l, Marinewater invertebrates  
REACH dossier information.

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: 84 mg/l, Scenedesmus subspicatus  
REACH dossier information.

#### 2-piperazin-1-ylethylamine

##### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 2190 mg/l, Pimephales promelas (Fat-head Minnow)  
REACH dossier information.

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 58 mg/l, Daphnia magna  
REACH dossier information.

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 72 hours: > 1000 mg/l, Selenastrum capricornutum  
REACH dossier information.

### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

### Ecological information on ingredients.

#### Butadiene-acrylonitrile co-polymer

**Persistence and degradability** There are no data on the degradability of this product.

### Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA

**Persistence and degradability** There are no data on the degradability of this product.

#### 2,4,6-tris(dimethylaminomethyl)phenol

**Biodegradation** Water - Degradation (%) 4: 28 days  
REACH dossier information.  
The product is not readily biodegradable.

#### 2-piperazin-1-ylethylamine

**Phototransformation** Water - DT<sub>50</sub> : 1.8 hours  
REACH dossier information.

## WEST SYSTEM G/flex 655 Hardener

**Biodegradation** Water - Degradation (%) 0: 28 days  
REACH dossier information.  
No biodegradation observed under test conditions.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not determined.

### Ecological information on ingredients.

#### Butadiene-acrylonitrile co-polymer

**Bioaccumulative potential** No data available on bioaccumulation.

#### Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA

**Bioaccumulative potential** No data available on bioaccumulation.

#### 2,4,6-tris(dimethylaminomethyl)phenol

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Pow:  $\geq 0.219$  REACH dossier information.

#### 2-piperazin-1-ylethylamine

**Bioaccumulative potential** The product is not bioaccumulating.

**Partition coefficient** log Pow: -1.48 REACH dossier information.

### 12.4. Mobility in soil

**Mobility** No data available.

### Ecological information on ingredients.

#### Butadiene-acrylonitrile co-polymer

**Mobility** No information available.

#### Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA

**Mobility** No information available.

#### 2,4,6-tris(dimethylaminomethyl)phenol

**Mobility** The product is water-soluble and may spread in water systems.

#### 2-piperazin-1-ylethylamine

**Mobility** The product is miscible with water and may spread in water systems.

**Henry's law constant**  $< 0 \text{ atm m}^3/\text{mol}$  @ 20°C Estimated value. REACH dossier information.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### Ecological information on ingredients.

## WEST SYSTEM G/flex 655 Hardener

### Butadiene-acrylonitrile co-polymer

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### Phenol, 2,4,6-Tris[(dimethylamino)methyl] reaction products with TETA

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 2,4,6-tris(dimethylaminomethyl)phenol

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 2-piperazin-1-ylethylamine

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**General information** The generation of waste should be minimised or avoided wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

**Disposal methods** Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

### **SECTION 14: Transport information**

**General** The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

No transport warning sign required.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

## WEST SYSTEM G/flex 655 Hardener

### Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

Not applicable.

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations

Health and Safety at Work etc. Act 1974 (as amended).  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].  
EH40/2005 Workplace exposure limits.

#### EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Commission Regulation (EU) No 2015/830 of 28 May 2015.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

### Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.  
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.  
IATA: International Air Transport Association.  
ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.  
IMDG: International Maritime Dangerous Goods.  
CAS: Chemical Abstracts Service.  
ATE: Acute Toxicity Estimate.  
LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.  
LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).  
EC<sub>50</sub>: 50% of maximal Effective Concentration.  
PBT: Persistent, Bioaccumulative and Toxic substance.  
vPvB: Very Persistent and Very Bioaccumulative.

### Classification abbreviations and acronyms

Eye Dam. = Serious eye damage  
Skin Corr. = Skin corrosion  
Skin Sens. = Skin sensitisation  
STOT RE = Specific target organ toxicity-repeated exposure  
STOT SE = Specific target organ toxicity-single exposure

## WEST SYSTEM G/flex 655 Hardener

<b>Key literature references and sources for data</b>	Source: European Chemicals Agency, <a href="http://echa.europa.eu/">http://echa.europa.eu/</a>
<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Eye Dam. 1 - H318: Skin Corr. 1B - H314: STOT RE 2 - H373: STOT SE 3 - H335: Skin Sens. 1 - H317: : Calculation method.
<b>Training advice</b>	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
<b>Revision date</b>	20/10/2021
<b>Revision</b>	13
<b>Supersedes date</b>	22/09/2021
<b>SDS number</b>	10622
<b>Hazard statements in full</b>	H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H361 Suspected of damaging fertility or the unborn child if swallowed. H372 Causes damage to organs (Respiratory tract) through prolonged or repeated exposure if inhaled. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.